

Saflok Quantum Pixel

dormakaba 

**NEW
FINISHES
&
LEVERS**



Overview

Saflok Quantum Pixel provides an easy-to-use, secure, and flexible solution that is both visually attractive and high-performing. With its electronics concealed within the door, the Quantum Pixel's visible hardware is minimal resulting in a lock design that integrates seamlessly with any hotel decor.

Mobile Access

The Quantum Pixel is equipped with Bluetooth Low Energy (BLE) Technology, meaning guests can safely use dormakaba Mobile Access Solution with their mobile device to access any door in the hotel equipped with Quantum Pixel.

Applications

- Ideal for new projects or when doors are being replaced
- Suitable for small to very large scale hotels
- Access control for guest rooms
- Interior door only

Security Features

- 1" solid deadbolt
- Staff monitoring – RFID keycard audits
- Tracking mortise for door ajar reporting
- Emergency key and electronic override
- Tamper Resistant

Low Maintenance

- AA alkaline; Batteries last up to 2 years
- Low battery indicator alerts staff
- Lock programming and audit records are not erased during battery replacement
- Service tray for easy battery access

Access Control Management Software

The Quantum Pixel lock is supported by dormakaba's access management software solution for both guest and staff access. Optionally, choose dormakaba's online access management solution for superior control and monitoring.

Mechanical Features

Description	Electronic mortise lockset with 1" (25.4mm) throw deadbolt and 5/8" (15.9mm) dead-locking latch bolt	
Reader cover	Polycarbonate. Color: black	
Handing	Factory-handed mortise (left, right, left reverse, right reverse)	
Lever	ADA Compliant.	
		
	Standard : Arc (Shown in Satin Brass), Apogee (Shown in Satin Brass), Continental (Shown in Bright Chrome), Elevon (Shown in Antique Copper), Gala (Shown in Black Lacquer), Troy. Customization: customized levers and other special lever designs are available upon request.	
Available Finishes	Standard finishes: Satin Chrome, Satin Brass, Bright Chrome, Bright Brass, Satin Nickel Special finishes: Antique Copper, Black Lacquer, Supreme Satin Chrome, and other special finishes are available upon request. For custom levers and finishes, please contact your dormakaba local sales representative	
Door Thickness	1.38" (35.1 mm) to 3.0" (77 mm). No mortise offset, no rabbeted doors. Wood or metal solid clad doors only (no hollow doors)	
Locking Options	ANSI lock case with 1" lock front mortise, Option: Standard, Door Ajar or Automatic Deadbolt, Door Ajar	
Online Configurations	Messenger LENS Ready	DAJ mortise (ANSI lock case)
	Messenger LENS Online	Lock controller board with Messenger LENS capability DAJ mortise (ANSI lock case)

Mobile Access Option (BLE)

BLE ready	Upgradeable to BLE with BLE module
BLE enabled	BLE module included, no further upgrades needed

Lock Operation

Date/Time Stamp	Real-time; date and hours/minutes
Interrogation	Obtain key usage reports from the lock by using a handheld unit at the door, or remotely using Messenger LENS
Keycards	Configurable expiration dates and can be made up to 10 days in advance without canceling current or arriving guests
Passage Mode	Set by authorized keycard or Messenger LENS system. Can also be configured to perform an automated/pre-defined passage mode time.
RFID Credentials Specifications	Two credential format options available: Mifare Classic or Mifare Plus- Mifare Classic (4byte NUID): Guest Keycards (Mini), Staff (4K & 1K) - Mifare Plus: Guest Keycards (Mifare Ultralight C, 7 Byte UID), Staff Keycards (Mifare Plus S 2K, 4 Byte NUID, Mifare Plus S 4K, 4 Byte NUID)
Audit Trail	Up to 4,000 events
Disability Feature	RCU readers required to interface with automatic power operated doors for special openings

Certifications & Testing

Accessibility Standard	Complies with ADA standards 2010 for accessible design
BHMA/ANSI	Grade One performance tests for ANSI/BHMA A156.13 - 2017 "American National Standard for Mortise Locks and Latches," and A156.25 - 2013 "American National Standard for Electrified Locking Devices." (Only locks tested and approved by non-biased third-party test lab are allowed in the "BHMA Certified Products Directory" found at www.buildershardware.com)
Fire Rating	Listed for 30 minute fire rating on a single-leave wooden composite doors in wooden frame with a thickness of 44 mm
Electronics	FCC Part 15 Class A and CE directive 2014/53/EU compliant
Environmental Operating Conditions	Indoor side: 32°F to 151°F (0°C to 66°C); 0% to 85% non-condensing humidity at 86°F (30°C); IP rating: IP54

